

Elevator calculation acc. EN81-1

Item 805

Elevator data

Nominal load	Q	kg	600	
Car weight	F	kg	800	(730 - 1936kg)
Counterweight	G	kg	1100	(50%)
Travelling speed	v	(V_3=)	m/s	1.00
Travel distance	H	m	30.0	
Suspension / (roping)	is		2	: 1
Machine at the top, above				
Shaft efficiency	etaS	%	82	
Number of pulleys	(ball bearing)		3	
Type of rope	WOLF PAWO F7			
Number of ropes	z		6	
Rope diameter	ds	mm	8	
Rope weight	s	kg	46	(0.258 kg/m)
Compensation rope weight	su	kg	0	
Car cable weight	HK	kg	15	
Rope span weight	R	kg	0	
Min. rope breaking load	B	N	40600	
Traction sheave diameter	Dtr	mm	320	
Sheave width		mm	110	(number of grooves

6)

Groove distance		mm	17.0	Standard
Angle of wrap minimum	min.	deg	180	
Undercutangle		deg	95	
Undercutwidth	b	mm	5.90	
Groove angle		deg	30	
Sheave profile:	circular undercut groove			

Traction, rope pressure, rope safety

Traction empty, on top, accelerating (1.18)
1.7236 <= 1.8399
Traction 150% nominal load, below, not moving
1.6299 <= 1.8399
Rope pressure $k <$ permissible rope pressure
5.29 < 9.00 N/mm²

Conditions according to EN81-1 or -20:
Load 125% 1.4935 <= 1.8582 (1)
Emergency stop 1.6270 <= 1.6759 (4)
with deceleration [m/s²]0.500
Blocked car 10.833 > 3.4528 (4)

Real safety factor > Minimum safety factor for ropes
33.27 > 12

Rope safety factor according to EN81-1 or -20:
NEQUIV = 09.7 NEQUIVT = 06.7 NEQUIVP = 03.0
Pulleys >= 320 mm, pulleys NPR = 0 NPS = 3
Rope safety nue = 33.3 > 18.5 (minSF)
Rope certification EN81

Traction conditions are fulfilled.
Rope safety conditions are fulfilled.

ZAlift - 20161219 - Machine dimensioning d3293873

Mechanical drive data

Machine manufactured by Ziehl-Abegg

Machine type SM 200.20C Gearless synchronous

Machine version ZAtop *

Traction sheave	mm	320
/110/17.0/6x8/U95		
Load output torque	Nm	373 (max. 396)
Real statical axle load	kg	1303 (max. 2440)

Brake data

brake Mayr ROBA-twinstop 350, 2x410 Nm, EU-BD 845 (ABV845 + ESV845)

Dual circuit disk brake, DC supply necessary

(308 Nm, 0.47 m/s², 1 m, 7228 J, 164 W)

2 x 410 Nm 207 V brake, with hand release, microswitch

Machine load data in the installation

Typical motor operating power	kW	2.8
Typ. operating current 15.7 A, Start. Current	24.2 A at acceleration	0.60 m/s ²
Start. Current	25.6 A at acceleration	0.7 m/s ²
Average power losses	0.69 kW = 2477.44 kJ/h	
Output speed	rpm	119
Load torque	Nm	373.8 (eff. 220.9)
Inertia of installation	kgm ²	17.19
240 Starts per hour	, 40 % required duty cycle at elevator operation	
Max. static load pulleys	10792 N, pulley speed	1.00 m/s

Selected ZIEHL-ABEGG motor

Motor type SM200.20C-20 - gearless

	Nameplate data		(Operating	
data)				
Rated voltage	V	360		
Rated frequency	Hz	20	(19.9)
Rated torque	Nm	330	(373.8)
Rated speed	rpm	120	(119.4)
Rated output power	kW	4.1	(4.7)
Rated current	A	12.8	(15.7)
Maximum torque	Nm	570	(570)
Current at maximum torque	A	28.5	(28.5)
Inertia of motor	kgm ²	0.160		
Possible acceleration	m/s ²	0.90		
(MKmax=280.0 Nm)				
Without cooling	(79)			
Dimension sheet A-M-6686, Motor construction type IMB3				
Motor with encoder ECN 1313-2048Endat				

Selected frequency inverter

Inverter ZAdyn 4CS017, Rated inverter current 17 A

mains current 12.5 A, 400 V, 8.2 kW, Max. 0.90 m/s²

Radio interference filter, integrated ; Line reactor, integrated

Brake resistance separate BR17-3 (or Recuperation: ZArec4C 013)

ASACOD.CO-02144340048